



BXCS650

**IN CEILING 6.5" SUBWOOFER
POWERED BY SONIC VORTEX®**

Our Sonic Vortex® technology generates rich, deep bass and effortless clarity from what most people would call a 'back box', but is not. It is actually a compact, integrated tuned enclosure. This patented technology is a 'twist' on Ported Transmission Line design, that optimizes air movement to produce astonishing sound. The enclosure also keeps sound from bleeding to other rooms while adding 6 to 9dB boost in mid-lower bass. Recommended crossover setting: 80Hz and below.



Optional EZBracket pre-construction bracket; use size "F" for this model.

- Woofer: 6.5" Fiberglass
- Frequency/Crossover Setting: 80Hz and below
- Surround: Butyl Rubber
- Speaker Weight: 7.1lbs (3.2 kg)
- Cutout: 8.4" (214 mm)
- Grill Diameter: 9.4" (239 mm)
- Depth: 6.8" (172 mm)
- Power Handling: 5-200W
- Impedance: 4Ω
- Installed Frequency Response: 40 Hz - 300 Hz
- Sensitivity: 90 db
- Grille: Magnetic Bezelless; White - Paintable
- Connector Type: Push Terminals
- Pre-construction Bracket: EZBracket Size: F

Multiple International Patents Awarded
Additional Patents Pending

